COFFEE PRO

COFFEE LABORATORY

MOISTURE-MAC



EASY TO USE

RUGGED PORTABLE DESIGN

NO SAMPLE PREPARATION REQUIRED

AVERAGING FACILITY

LANGUAGE OPTIONS IN ENGLISH, SPANISH, PORTUGESE, GERMAN, AND FRENCH

MULTI POINT CALIBRATION AVAILABLE

HIGHER FREQUENCY CAPACITIVE CIRCUIT FOR ENHANCED ACCURACY

ROBUST TEMPERATURE COMPENSATION CIRCUIT

SPECIFICATIONS:

Operating Range (Moisture): 5% to 40% depending on grain tested in ten seconds.

Operating Range (Temperature): 32° - 113° F (0° - 45° C).

Repeatability: moisture range

+/- 0.5% in normal

Accuracy: moisture range +/- 0.5% in normal

Display Resolution:

0.1% moisture.

2 year warranty in North America and 1 year overseas.

No charts to read or complicated instructions, meaning virtually no operator training is required. No moving parts reduces down time for calibrations, adjustments, or repairs

Compact design is great for testing for coffee or grain moisture at remote locations. Calibrations include green coffee, parchment coffee (Pergamino), and cocoa. Raw data values (Bit Values) may be used with a spreadsheet to establish moisture curves for any suitable commodity

