

**COFFEE-PRO
MOISTURE-MAC**



- EASY TO USE**
- RUGGED PORTABLE DESIGN**
- NO SAMPLE PREPARATION REQUIRED**
- AVERAGING FACILITY**
- LANGUAGE OPTIONS IN ENGLISH, SPANISH, PORTUGUESE, GERMAN, AND FRENCH**
- MULTI POINT CALIBRATION AVAILABLE**
- HIGHER FREQUENCY CAPACITIVE CIRCUIT FOR ENHANCED ACCURACY**
- ROBUST TEMPERATURE COMPENSATION CIRCUIT**

QUOTE REQUEST ✓

BUY ONLINE ✓

SPECIFICATIONS:

- Operating Range (Moisture):** 5% to 40% depending on grain tested in ten seconds.
- Operating Range (Temperature):** 32° - 113° F (0° - 45° C).
- Repeatability:** +/- 0.5% in normal moisture range
- Accuracy:** +/- 0.5% in normal moisture range
- Display Resolution:** 0.1% moisture.
- 2 year warranty in North America and 1 year overseas.**

No charts to read or complicated instructions, meaning virtually no operator training is required. No moving parts reduces down time for calibrations, adjustments, or repairs

Compact design is great for testing for coffee or grain moisture at remote locations. Calibrations include Arabica, Robusta, Dry Cherry, Parchment, and Cocoa. Raw data values (Bit Values) may be used with a spreadsheet to establish moisture curves for any suitable commodity



Deluxe Model Available with field density scale, and hard carry case

Packed Dimensions & Weight
 Moisture Mac L 228 mm x W 127 mm x H 178 mm Weight 1.4 kg
 Moisture Mac Kit L 407 mm x W 407 mm x H 204 mm Weight 3.2 kg