



TECHNICAL DATA

| | |
|------------------------|----------------------|
| Hopper Capacity | 1.3 lbs |
| Grinding Capacity | 1,5 - 3,0 g/sec |
| Voltage | 100-120 V |
| Frequency / Phases | 60 Hz / Single-Phase |
| Grinding Disc Diameter | 65 mm |
| Dimensions (w x d x h) | 3.6" x 10.6" x 16.9" |
| Net Weight | 13.2 lbs |
| Shipping Weight | 19.8 lbs |

EQUIPMENT FEATURES

| | |
|---------------------|---|
| Port-a-filter rest | ● |
| Shot counter | ● |
| External display | ● |
| Overload protection | ● |
| Display | ● |

LISTINGS

CE, UL, NSF

K30 Vario Single Espresso Grinder



TECHNICAL DATA

| | |
|------------------------|----------------------|
| Hopper Capacity | 3.3 lbs |
| Grinding Capacity | 3.6-4.8 g/sec |
| Voltage | 100-115 V |
| Frequency / Phases | 60 Hz / Single-Phase |
| Grinding Disc Diameter | 65 mm |
| Dimensions (w x d x h) | 9.5" x 12.6" x 21.7" |
| Net Weight | 28.7 lbs |
| Shipping Weight | 33.0 lbs |

EQUIPMENT FEATURES

| | |
|-------------------------------|---|
| Universal Port-a-Filter Rests | ● |
| Overload Protection | ● |
| Shot Counter | ● |

SPECIAL FEATURES

| | |
|------------------|---|
| Different Colors | ● |
| Tamper Static | ● |

LISTINGS

UL, NSF

K30 Twin Espresso Grinder



TECHNICAL DATA

| | |
|------------------------|----------------------|
| Hopper Capacity | 2 x 1.8 lbs |
| Grinding Capacity | 3.6-4.8 g/sec |
| Voltage | 100-115 V |
| Frequency / Phases | 60 Hz / Single-Phase |
| Grinding Disc Diameter | 2 x 65 mm |
| Dimensions (w x d x h) | 14.6" x 11.8" x 22" |
| Net Weight | 57.3 lbs |
| Shipping Weight | 63.9 lbs |

EQUIPMENT FEATURES

| | |
|------------------------------------|---|
| Two Universal Port-a-Filter Rests | ● |
| Two Simultaneously Usable Grinders | ● |
| Overload Protection | ● |
| Shot Counter | ● |
| Fan Cooling | ● |

SPECIAL FEATURES

| | |
|-----------------|---|
| Flexible Design | ● |
| Tamper Static | ● |

LISTINGS

UL, NSF

EK43 / EKK43

RETAIL GRINDER

EK 43 2,950.00 US\$ | EKK 43 3,695.00 US\$



| TECHNICAL DATA | EK43 | EKK43 |
|------------------------------------|---|----------------------|
| Hopper Capacity | 2.2 lbs | 2 x 2.2 lbs |
| Grinding Capacity – fine to medium | 2.6-3.3 lbs/min | 1.9-2.2 lbs/min |
| Voltage | 100-115 V | 100-115 V |
| Frequency / Phases | 60 Hz / Single-Phase | 60 Hz / Single-Phase |
| Grinding Disc Diameter | 98 mm | 98 mm |
| Dimensions (w x d x h) | 9.0" x 16.1" x 30.0" | 9.0" x 23.2" x 30.0" |
| Net Weight | 52.9 lbs | 61.7 lbs |
| Shipping Weight | 57.3 lbs | 72.8 lbs |
| EQUIPMENT FEATURES | | |
| Bag Holder | ● | ● |
| Hopper Magnet | ● | ● |
| Overload Protection | ● | ● |
| Knock-off Device | ● | ● |
| SPECIAL FEATURES | | |
| Real Turkish Fine Grinding | ● | ● |
| Other Hopper | 6.6 lbs | 6.6 lbs |
| Espresso Grinding | ● | ● |
| Other Grinding Goods | Coffee, spices, grains, poppy seed, linseed | |
| LISTINGS | | |
| | UL | UL |

VTA 6S / VTA 6SW

RETAIL GRINDER

VTA 6S 4,500.00 US\$ | VTA 6SW 4,500.00 US\$



| TECHNICAL DATA | VTA6 S | VTA6 SW |
|------------------------------------|----------------------|----------------------|
| Hopper Capacity | 2.2 lbs | 2.2 lbs |
| Grinding Capacity – fine to medium | 5.5-6.1 lbs/min | 3.1-3.5 lbs/min |
| Voltage | 208 V | 230 V |
| Frequency / Phases | 60 Hz / Three-Phase | 60 Hz / Single-Phase |
| Grinding Disc Diameter | 120 mm | 120 mm |
| Dimensions (w x d x h) | 4.6" x 15.0" x 24.8" | 4.6" x 15.0" x 24.8" |
| Net Weight | 92.6 lbs | 92.6 lbs |
| Shipping Weight | 101.4 lbs | 101.4 lbs |
| EQUIPMENT FEATURES | | |
| Bag Holder / Shaker | ● | ● |
| Hopper Magnet | ● | ● |
| Overload Protection | ● | ● |
| SPECIAL FEATURES | | |
| Real Turkish Fine Grinding | ● | ● |
| Base Height Extension | 3.9" | 3.9" |
| Other Hopper | 6.6 lbs | 6.6 lbs |
| Frequency Converter | ● | ● |
| Other Voltages / Frequency | ● | ● |
| Tungsten Carbide Discs | ● | ● |
| Listings | UL, NSF | UL, NSF |

ProM - Allround Grinder

FOOD SERVICE GRINDER

1,495.00 US\$



| TECHNICAL DATA | |
|---------------------------|-------------------------|
| Hopper Capacity | approx. 0.57 lbs |
| Grinding Capacity | approx. 1.5 - 8.5 g/sec |
| Voltage | 100-120 V |
| Frequency / Phases | 60 Hz / Single-Phase |
| Grinding Disc Diameter | 65 mm |
| Dimensions (w x d x h) | 3.6" x 10.6" x 16.6" |
| Net Weight | 13.2 lbs |
| Shipping Weight | 19.8 lbs |
| EQUIPMENT FEATURES | |
| Port-a-filter rest | ● |
| Ground coffee container | ● |
| Overload protection | ● |
| SPECIAL FEATURES | |
| External display | ● |
| 600 g hopper | ● |
| LISTINGS | |
| | CE, UL, NSF, Jet |



| TECHNICAL DATA | GSS1 |
|------------------------------------|----------------------|
| Hopper Capacity | 1.1 lbs |
| Grinding Capacity – fine to medium | approx. 2.0 lbs/min |
| Voltage | 100-115 V |
| Frequency / Phases | 60 Hz / Single-Phase |
| Grinding Disc Diameter | 90 mm |
| Dimensions (w x d x h) | 7.9" x 16.4" x 22.9" |
| Net Weight | 61.7 lbs |

EQUIPMENT FEATURES

| | |
|--------------------------|---|
| Hopper magnet | ● |
| Bag in place recognition | ● |
| Bag shaker | ● |
| Thermal protector | ● |
| Cooling fan Ventilator | |

| | |
|-----------------|---------|
| LISTINGS | UL, NSF |
|-----------------|---------|

Tanzania

**TECHNICAL DATA**

| | |
|------------------------------------|---------------------------|
| Hopper Capacity | 1.6 lbs |
| Grinding Capacity – fine to medium | 1.2 - 2.0 lbs/min @ 60 Hz |
| Voltage | 100 - 115 V |
| Frequency | 60 Hz |
| Grinding Disc Diameter | 80 mm |
| Dimensions (w x d x h) | 8.1" x 11.6" x 24.9" |
| Net Weight | 35.3 lbs |
| Shipping Weight | 40 lbs |

EQUIPMENT FEATURES

| | |
|-----------------------|---|
| Magnetic Disc Carrier | ● |
| Bag Clamping | ● |
| Bag Shaker | ● |
| Motor Ventilation | ● |

SPECIAL FEATURES

| | |
|----------------------------|---------|
| Real Turkish Fine Grinding | ● |
| Other Hopper | 3.3 lbs |

| | |
|-----------------|----|
| LISTINGS | CB |
|-----------------|----|

Kenia / Guatemala

**TECHNICAL DATA**

| | Kenia | Guatemala |
|------------------------------------|----------------------|----------------------|
| Hopper Capacity | 1.1 lbs | 1.1 lbs |
| Grinding Capacity – fine to medium | 1.1 - 1.6 lbs/min | 1.8 - 2.0 lbs/min |
| Voltage | 100 - 115 V | 100 - 115 V |
| Frequency / Phases | 60 Hz / Single-Phase | 60 Hz / Single-Phase |
| Grinding Disc Diameter | 65 mm | 71 mm |
| Dimensions (w x d x h) | 8.7" x 13" x 24.4" | 8.7" x 13" x 24.4" |
| Net Weight | 39.7 lbs | 39.7 lbs |
| Shipping Weight | 52.9 lbs | 52.9 lbs |

EQUIPMENT FEATURES

| | | |
|---------------------|---|---|
| Bag Holder | ● | ● |
| Bag Shaker | — | ● |
| Hopper Magnet | ● | ● |
| Overload Protection | ● | ● |
| Knock-off Device | ● | ● |

SPECIAL FEATURES

| | | |
|--------------------------------|---------|---------|
| Other Voltages (also 3~ Motor) | ● | ● |
| Base Height Extension | 5.1" | 5.1" |
| Large Hopper | 2.2 lbs | 2.2 lbs |

Guatemala Lab / Guatemala Filter

SPECIAL GRINDER

2,695.00 US\$



| TECHNICAL DATA | Guatemala Lab | Guatemala Filter |
|------------------------------------|----------------------|----------------------------|
| Hopper Capacity | 1.1 lbs | 1.1 lbs |
| Grinding Capacity – fine to medium | approx. 1.6 lbs/min | approx. 1.1 - 1.54 lbs/min |
| Voltage | 100-115 V | 100-115 V |
| Frequency / Phases | 60 Hz / Single-Phase | 60 Hz / Single-Phase |
| Grinding Disc Diameter | 65 mm | 65 mm |
| Dimensions (w x d x h) | 8.7" x 13.0" x 24.4" | 8.7" x 14.1" x 24.4" |
| Net Weight | 39.7 lbs | 41.8 lbs |
| Shipping Weight | 52.9 lbs | 55.0 lbs |
| EQUIPMENT FEATURES | | |
| Knock-off Device | ● | |
| Metal Dosing Cup | ● | ● |
| Hopper Magnet | ● | ● |
| Overload Protection | ● | ● |
| Various Brew Basket holder | | ● |
| SPECIAL FEATURES | | |
| Convertible to Gua F | ● | |
| Timer | | ● |
| Large hopper | ● | ● |
| LISTINGS | | |
| | UL, NSF | UL, CSA |

DK15 L / DK15 LH

INDUSTRIAL GRINDER

DK15 L 10,200.00 US\$ | DK15 LH 12,200.00 US\$



| TECHNICAL DATA | |
|------------------------------------|---|
| Hopper Capacity | 66 lbs |
| Grinding Capacity – fine to medium | 265-287 lbs/h |
| Voltage | 208-220 V |
| Frequency / Phases | 60 Hz / Three-Phase |
| Grinding Disc Diameter | 130 mm |
| Dimensions (w x d x h) | 31.1" x 48.4" x 61.0" |
| Net Weight | 291.0 lbs |
| Shipping Weight | 478.4 lbs |
| EQUIPMENT FEATURES | |
| Container | 200l, mobile |
| Hopper Magnet | ● |
| Overload Protection | ● |
| SPECIAL FEATURES | |
| Other Grinding Goods | Coffee, spices, grains, poppy seed, linseed |
| Tungsten Carbide Discs | ● |
| Pod-Grinding | ● |
| LISTINGS | |
| | - |

DK27 LV / DK27 LVH

INDUSTRIAL GRINDER

DK27 LV 17,400.00 US\$ | DK27 LVH 20,800.00 US\$



| TECHNICAL DATA | |
|------------------------------------|---------------------------------|
| Hopper Capacity | 66 lbs |
| Grinding Capacity – fine to medium | 620-660 lbs/h |
| Voltage | 208-220 V |
| Frequency / Phases | 60 Hz / Three-Phase |
| Grinding Disc Diameter | 180 mm |
| Dimensions (w x d x h) | 31.1" x 48.4" x 63.0" |
| Net Weight | 341.7 lbs |
| Shipping Weight | 529.1 lbs |
| EQUIPMENT FEATURES | |
| Container | 200l, mobile |
| Hopper Magnet | ● |
| Overload Protection | ● |
| SPECIAL FEATURES | |
| Turkish Grinding | ● |
| Other Grinding Goods | Coffee, spices, grains, linseed |
| Tungsten Carbide Discs | ● |
| Pod-Grinding | ● |
| Fan Cooling | ● |